

Permatex, Inc.  
 10 Columbus Blvd.  
 Hartford, CT 06106 USA  
 Telephone: 1-87-Permatex  
 (877) 376-2839  
 Emergency: 800-255-3924  
 International Emergency: 813-248-0585

## Material Safety Data Sheet

### 1. PRODUCT IDENTIFICATION

**Product Name:** 99GA HIGH TACK SPRAY-A-GASKET 4.75 OZ AE  
**Item No:** 80064  
**Product Type:** Aerosol sealant

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Weight Percent	ACGIH TLV:	OSHA PEL:
BUTANE 106-97-8	>25	1000 ppm TWA	800 ppm TWA; 1900 mg/m <sup>3</sup> TWA
ACETONE 67-64-1	>20	500 ppm TWA; 750 ppm STEL	1000 ppm TWA; 2400 mg/m <sup>3</sup> TWA
PROPANE 74-98-6	<15	1000 ppm TWA	1000 ppm TWA; 1800 mg/m <sup>3</sup> TWA
DICHLOROMETHANE 75-09-2	<30	50 ppm TWA; 174 mg/m <sup>3</sup> TWA	25 ppm TWA; 125 ppm STEL (15 min. TWA)
ETHYL ACETATE 141-78-6	<5	400 ppm TWA	400 ppm TWA; 1400 mg/m <sup>3</sup> TWA
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH. 64742-89-8	<5	Not Listed	Not Listed

### 3. HAZARDS IDENTIFICATION

**Toxicity:** May cause nose, throat and respiratory irritation. May cause eye and skin irritation. Intentional misuse by concentrating and inhaling the vapor may be harmful or fatal. Excessive inhalation causes headache, dizziness, nausea, and incoordination. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage (sometimes referred to as "solvent" or "painter's syndrome"). Symptoms include fatigue, concentration difficulties, anxiety, depression, rapid mood swings, and short-term memory loss. Ethyl acetate may cause anemia. Methylene chloride will have an effect on the cardiovascular system. Inhalation of high concentrations of Methylene chloride over long periods of time has caused cancer in laboratory animals. Long term exposure to high concentrations of vapor may cause lung, liver or kidney damage.

**Primary Routes of Entry:** Eye and skin contact, ingestion, inhalation

**Signs and Symptoms of Exposure:** Excessive overexposure may cause giddiness, dizziness, headache, nausea and in extreme cases, unconsciousness and respiratory depression. Inhaling may cause mild irritation to the nose, throat and respiratory tract and may result in central nervous system (CNS) depression. May cause pain, redness or swelling of the eyes and excessive blinking and tear production. Skin: Exposure may cause mild skin irritation. Prolonged or repeated exposure may dry the skin. Symptoms may include redness, burning, drying, cracking and skin burns. Preexisting skin disorders may be aggravated by exposure. Skin absorption is possible, but harmful effects are not expected from this route under normal conditions of handling and use. Swallowing: This material can enter the lungs during swallowing or vomiting and cause lung inflammation and/or damage. Aspiration into the lungs can cause chemical pneumonia which can be fatal.

Ingredient	Weight Percent	NTP	ACGIH Carcinogens	IARC
ACETONE 67-64-1	>20	Not known	A4 - Not Classifiable as a Human Carcinogen	Not known
DICHLOROMETHANE 75-09-2	<30	Group 2: Suspect Carcinogen	A3 - Animal Carcinogen	Group 2B: Monograph 41, Supplement 7, Monograph 71; 1998

**Medical Conditions Recognized as Being Aggravated by Exposure:** Cardiovascular problems may be aggravated by overexposure to methylene chloride. Persons with preexisting respiratory, liver, kidney, eye or skin diseases may be adversely affected.

#### **4. FIRST AID MEASURES**

**Ingestion:** Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

**Inhalation:** Move to fresh air in case of accidental inhalation of vapors. Oxygen or artificial respiration if needed. Obtain medical attention.

**Skin Contact:** Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

#### **5. FIRE FIGHTING MEASURES**

**Flash Point (°F/C):** Extremely Flammable based on flame projection test

**Recommended Extinguishing Media:** Water fog, carbon dioxide, foam, dry chemical.

**Special Fire-Fighting Procedures:** Firefighters should wear self-contained breathing apparatus. Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

**Hazardous Products of Combustion:** Carbon dioxide, Carbon monoxide, Chlorine, Hydrogen chloride, Phosgene

**Unusual Fire/Explosion Hazards:** Contents under pressure. Exposure to temperatures over 120 degrees F. may cause bursting or venting. Use equipment or shielding to protect personnel from bursting containers.

**Lower Explosive Limit:** 1.8

**Upper Explosive Limit:** 9.5

#### **6. ACCIDENTAL RELEASE MEASURES**

**Spill Procedures:** Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

#### **7. HANDLING AND STORAGE**

**Storage:** Store away from heat, sparks or open flame. Do not store at temperatures above 120 degrees F. Exposure to high temperatures may cause container to burst.

**Handling:** Avoid breathing vapors, if exposed to high vapor concentration, leave area at once. Avoid contact with skin and eyes. Do not puncture or incinerate container. Do not use near heat, sparks or open flame. Intentionally concentrating and inhaling the vapor may be harmful or fatal. Use in a well ventilated area to prevent irritation by vapors. Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet.

#### **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Eyes:** Safety glasses

**Skin:** Rubber or plastic gloves.

**Ventilation:** General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.

**Respiratory Protection:** An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the applicable limits.

#### **9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance:** Red liquid

**Odor:** Solvent

**Boiling Point:** Not determined

**pH:** Does not apply

**Solubility in Water:** Nil

**Specific Gravity:** 0.83-1.00 (concentrate)

**VOC Content(Wt.%):** 59.5% by weight

**Vapor Pressure:** 41-51 psig

**Vapor Density (Air=1):** >1 (air = 1)

**Evaporation Rate:** >1 (butyl acetate = 1)

#### **10. STABILITY AND REACTIVITY**

**Chemical Stability:** Stable at normal conditions

**Hazardous Polymerization:** WILL NOT OCCUR.

**Incompatibilities:** Strong oxidizers, strong alkalis, reactive metals

**Conditions to Avoid:** Keep away from heat, sparks and open flame

**Product Name:** 99GA HIGH TACK SPRAY-A-GASKET  
4.75 OZ AE

**Item No:** 80064

## **10. STABILITY AND REACTIVITY**

**Hazardous Products of Combustion:**

Carbon dioxide, Carbon monoxide, Chlorine, Hydrogen chloride, Phosgene

## **11. TOXICOLOGICAL INFORMATION**

See Section 3

## **12. ECOLOGICAL INFORMATION**

No data available

## **13. DISPOSAL CONSIDERATIONS**

**Recommended Method of Disposal:** Dispose of in accordance with local, state and federal regulations. This container may be recycled in aerosol recycling centers. Before offering for recycling, empty the can by using the product according to the label. If recycling is not available, wrap the container and discard in the trash.

**US EPA Waste Number:** D001/F002 - Hazardous waste per 40CFR 261.21 and 261.31 (Methylene Chloride)

## **14. TRANSPORTATION INFORMATION**

**DOT (49CFR 172)**

### **Domestic Ground Transport**

<b>DOT Shipping Name:</b>	CONSUMER COMMODITY
<b>Hazard Class:</b>	ORM-D
<b>UN/ID Number:</b>	None
<b>Marine Pollutant:</b>	None

### **IATA**

<b>Proper Shipping Name:</b>	Aerosols, flammable, containing substances in Division 6.1, Packing Group III
<b>Class or Division:</b>	Division 2.1, Subsidiary Risk 6.1
<b>UN/NA Number:</b>	UN 1950

### **IMDG**

<b>Proper Shipping:</b>	Aerosols
<b>Hazard Class:</b>	Class 2, 6.1
<b>UN Number:</b>	UN 1950

## **15. REGULATORY INFORMATION**

**SARA 313 Chemicals:** The following component(s) is listed as a SARA Section 313 Toxic Chemical.

DICHLOROMETHANE

### **CALIFORNIA PROP 65:**

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

### **TSCA Inventory Status:**

**Listed on Inventory:** YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

## **16. OTHER INFORMATION**

**Estimated NFPA Rating:** HEALTH 3, FLAMMABILITY 4, REACTIVITY 0

**Estimated HMIS Classification:** HEALTH 3, FLAMMABILITY 4, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

**Prepared By:** Denise Boyd, Health and Safety Manager  
**Company:** Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

**Revision Date:** January/09/2007

**Revision Number:** 5