








Material Safety Data Sheet

WHMIS (Pictograms)	WHMIS (Classification)	Personal Protective Equipment
 	Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). Class D-1B: Material causing immediate and serious toxic effects (TOXIC). Class D-2A: Material causing other toxic effects (VERY TOXIC). Class D-2B: Material causing other toxic effects (TOXIC).	  

Section 1. Product and Company Identification

Product Name / Trade name	Windshield Washer -35°C	Associated Product's Item Code	WIP-15215
Synonym	Not available.	CAS #	Mixture.
Chemical Family	Alcohol (solution).	Validation Date	7/19/2006.
Chemical Formula	Not applicable.	Print Date	7/19/2006.
Manufacturer	Recochem Inc. 850 Montee de Liesse Montreal, Quebec 514-341-3550	In Case of Emergency	Recochem Inc. Communications and Regulatory Affairs Department (905) 791-1788
Material Uses	Consumer products: Windshield de-icing fluid.		

Section 2. Hazardous Ingredients

Name	CAS #	% by Weight	Exposure Limits	
			Canadian Values (ACGIH)	U.S. Values (OSHA)
Methanol	67-56-1	40-50	ACGIH (Canada, 2003). Skin TWA: 200 ppm 8 hour(s). STEL: 250 ppm 15 minute(s). TWA: 260 mg/m ³ 8 hour(s). STEL: 328 mg/m ³ 15 minute(s).	Methanol OSHA (United States, 2003). TWA: 200 ppm 8 hour(s). TWA: 260 mg/m ³ 8 hour(s).

Section 3. Hazard Identification

Emergency Overview	DANGER! POISON FLAMMABLE. VAPOUR MAY CAUSE NEAR INVISIBLE FLASH FIRE. MAY BE FATAL IF SWALLOWED. Keep away from heat, sparks and flame. Do not ingest. Avoid breathing vapour or mist. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.
Potential Acute Health Effects	See Section #11: "Toxicological Information" for further human health effects. Extremely dangerous in case of ingestion. Hazardous in case of inhalation. Slightly hazardous in case of skin contact (irritant, permeator), of eye contact (irritant). Non-sensitizer for skin. Severe over-exposure can result in death.
Note to Physician	Acute exposure to methanol, either through ingestion or breathing high airborne concentrations can result in symptoms appearing between 40 minutes and 72 hours after exposure. Symptoms and signs are usually limited to CNS, eyes and gastrointestinal tract. Because of the initial CNS's effects of headache, vertigo, lethargy and confusion, there may be an impression of ethanol intoxication. Blurred vision, decreased acuity and photophobia are common complaints. Treatment with ipecac or lavage is indicated in any patient presenting within two hours of ingestion. A profound metabolic acidosis occurs in severe poisoning and serum bicarbonate levels are a more accurate measure of severity than serum methanol levels. Treatment protocols are available from most major hospitals and early collaboration with appropriate hospitals is recommended.

Continued on Next Page



Section 4. First Aid Measures

Eye Contact	IMMEDIATELY flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek medical attention.
Skin Contact	Gently and thoroughly wash the contaminated skin with running water and non-abrasive soap. If irritation persists, seek medical attention. Wash contaminated clothing before reusing.
Inhalation	Allow the victim to rest in a well ventilated area. Seek medical advice.
Ingestion	Do not induce vomiting. Have conscious person drink several glasses of water or milk. SEEK IMMEDIATE MEDICAL ATTENTION.

Section 5. Fire Fighting Measures

Products of Combustion	These products are carbon oxides (CO, CO ₂).
Fire Fighting Media and Instructions	SMALL FIRE: Use DRY chemicals, CO ₂ , alcohol foam or water spray. LARGE FIRE: Use alcohol foam, water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, auto-ignition or explosion.
Fire Hazards	Combustible liquid and vapor.
Explosion Hazards	No additional remark.

Section 6. Accidental Release Measures

Small Spill and Leak	Mop up, or absorb with an inert DRY material and place in an appropriate waste disposal container.
Large Spill and Leak	Flammable liquid. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Place in appropriate container and dispose of in accordance with regional regulations.

Section 7. Handling and Storage

Handling	S18- Handle and open container with care. Avoid all possible sources of ignition (spark or flame). After handling, always wash hands thoroughly with soap and water.
Storage	See Section #10 for applicable incompatible materials. Store and use away from heat, sparks, open flame, or any other ignition source. Keep away from sources of ignition. Keep away from incompatibles. Keep in a cool, well-ventilated place.

Section 8. Exposure Controls, Personal Protection

Engineering Controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the workstation location.
Personal Protection	
<i>Eyes</i>	Splash goggles.
<i>Body</i>	No special protective clothing is required.
<i>Respiratory</i>	Wear appropriate respirator when ventilation is inadequate.
<i>Hands</i>	Gloves (impervious).

Continued on Next Page

**Section 9. Physical and Chemical Properties**

Physical State and Appearance	Liquid.	Odour	Alcohol. (Slight.)
Molecular Weight	Not applicable.	Taste	Not available.
pH	8 to 10.5 [Basic.]	Colour	Blue.
Boiling/Condensation Point	64.5 to 100°C (148.1 to 212°F)	Volatility	40 to 50% (w/w).
Melting/Freezing Point	-35°C (-31°F)	Evaporation Rate	2.1 compared to Butyl acetate.
Specific Gravity	0.9 to 0.95 (Water = 1)	Odour Threshold	The highest known value is 2000 ppm (Methanol)
Vapour Pressure	<12.8 kPa (at 20°C)	Viscosity	Not available.
Vapour Density	<1.11 (Air = 1)	Solubility	Soluble in water.
VOC Content		Other Properties	Not available.
The Product is:	Flammable.		
Auto-ignition Temperature	385°C (725°F)		
Flash Point	Closed cup: 28°C (82.4°F). (Tagliabue.)		
Flammable Limits	LOWER: 6% UPPER: 36%		
Fire Hazards in Presence of Various Substances	Product may sustain a flame when source of ignition applied.		

Section 10. Stability and Reactivity

Stability	The product is stable.
Conditions of Instability	Not available.
Incompatibility with Various Substances	Slightly reactive to reactive with oxidizing agents, acids, alkalis.

Section 11. Toxicological Information

Routes of Entry	Absorbed through skin. Inhalation. Ingestion.
Toxicity to Animals	Acute oral toxicity (LD50): 5600-13000 mg/kg [Rat] (Methanol) Acute dermal toxicity (LD50): 15840 mg/kg [Rabbit] (Methanol) Acute toxicity of the vapor (LC50): 64000 ppm 4 hours [Rat] (Methanol)
Acute Effects on Humans	
<i>Eyes</i>	Slightly hazardous in case of eye contact (irritant).
<i>Skin</i>	Very slightly to slightly dangerous in case of skin contact (irritant, permeator). Non-sensitizer for skin. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.
<i>Inhalation</i>	Hazardous in case of inhalation.

Continued on Next Page



Ingestion Extremely hazardous in case of ingestion. May be fatal if swallowed. Ingestion may cause blindness.

Chronic Effects on Humans

Very hazardous in case of ingestion.
Slightly hazardous in case of skin contact (irritant).
Non-sensitizer for skin.
CARCINOGENIC EFFECTS: Classified A5 (Not suspected for human) by ACGIH, 4 (Probably not for human) by IARC, None. by OSHA.
MUTAGENIC EFFECTS: Not available.
TERATOGENIC EFFECTS: Teratogenic in mice at levels below maternal toxicity.
DEVELOPMENTAL TOXICITY: Fetotoxic in mice at levels below maternal toxicity.
Repeated exposure to a highly toxic material may produce general deterioration of health by an accumulation in one or many human organs.

Section 12. Ecological Information

Ecotoxicity

For accidental discharges into environment, see Section #6: "Accidental Release Measures" for suggested instructions.

No additional information.

Section 13. Disposal Considerations

Waste Information

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

Section 14. Transport Information

Canada Transportation of Dangerous Goods (TDG) Information

Primary Class	Not applicable.
Subsidiary Class (if applicable)	Not applicable.
Proper shipping name	Windshield washer antifreeze, Alcohol exempt.
Hazard Identification	Not applicable.
Number	
Packing Group	Not applicable.
Special Provisions	This product meets the requirements for exemption under TDG regulation special provisions, part 1, section 1.37: Class 3, Flammable liquids: Alcohol Exemption.

No placard (handling and hazard label) required.

International Maritime Dangerous Goods (IMDG) Transportation Information

Primary Class	Class 3: Flammable liquid.
Subsidiary Class (if applicable)	-
Proper shipping name	Alcohols, n.o.s. (Methanol)
Hazard Identification	UN 1987
Number	
Packing Group	III
Marine Pollutant	Not pollutant.
Special Provisions	Remarks In a means of containment of 5 L capacity or less this product is classified as a "Limited Quantity".



No placard (handling and hazard label) required.

United States Department of Transportation (DOT) Information

Continued on Next Page




Primary Class	Class 3: Flammable liquid.
Subsidiary class (if applicable)	-
Proper shipping name	Alcohols, n.o.s. (Methanol)
Hazard Identification Number	UN 1987
Packing Group	III
Special Provisions	Containers of 5 L or less ship as: Class: ORM-D Name: Consumer Commodity



International Air Transport Association (IATA) For air shipment classification and associated regulations, please refer to the latest edition of IATA Dangerous Goods Regulations.

Section 15. Other Regulatory Information and Pictograms

WHMIS Classification (Canada) Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F).
Class D-1B: Material causing immediate and serious toxic effects (TOXIC).
Class D-2A: Material causing other toxic effects (VERY TOXIC).
Class D-2B: Material causing other toxic effects (TOXIC).



Canada Domestic Substances List (DSL) Status This product and/ or all of its components are on the DSL.


HCS Classification (U.S.A.) Flammable liquid

U.S.A. Regulatory Lists This product and/ or all of its components are on the TSCA inventory list.

Hazardous Material Information System (U.S.A.)

Health	2
Flammability	2
Reactivity	0
Personal Protection	B

National Fire Protection Association (U.S.A.)



Section 16. Other Information

Validated and verified by Compliance and Technical Information Manager on 7/19/2006.

Printed 7/19/2006.

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

MSDS are available at www.recochem.com